

## CLAIMS

1. Packaging unit (1) for a flowable product, comprising first and second walls (2, 3) at least one (3) of which is concave and which are sealingly joined along their respective edges and define therebetween a cavity containing the flowable product, at least one of said walls (2, 3) being provided with a severing indicating means (8), severing along a line indicated by said severing indicating means (8) and extending from side-to-side across the packaging unit (1) opening a product outlet portion (6) of said cavity, characterized in that said severing indicating means (8) has over at least one of two end zones thereof at respective opposite sides (9) of said unit (1) a curvedly convex profile projecting away from said cavity.

2. Packaging unit according to claim 1, wherein said indicating means (8) comprises an incision (8) defining a predetermined fracture line.

3. Packaging unit according to claim 1 or 2, wherein said indicating means (8) has a curvedly convex profile from one of said sides (9) to the other of said sides (9).

4. Packaging unit according to claim 1 or 2, wherein said indicating means (8) has a rectilinear middle zone.

5. Packaging unit according to any preceding claim, wherein at at least one end of said indicating means (8) is a recess (11) in said respective edges and to the base of which said indicating means (8) extends.

WO 97/48619

PCT/EP97/03100

7

6. Packaging unit according to claim 5, wherein the or each recess (11) has a substantially rectilinear boundary portion defining, together with said indicating means (8), a significantly obtuse angle.